

COMMERCIAL POLYTUNNELS...



All Premier Polytunnels' Commercial Polytunnels are supplied as a complete unit ready for assembly onto a soil base. Our Commercial Polytunnel kits include an all-steel framework, made using 50mm diameter Z35 high tensile galvanised steel hoops, and including foundation tubes, corner stabilisers, central ridge bar, and (on 18ft wide and above) roof stabilisers. Our Commercial Polytunnels are supplied as standard with a NEW 5-layer, 720 gauge/180 micron Thermal Anti Drip polythene cover with a 5-year warranty against UV degradation. Double hinged doors with an opening of 5ft 11in are also supplied as standard at each end of the polytunnel.

A full range of additions are also available and are highly recommended to enable you to customise and enhance your 'Premier' polytunnel to suit the needs of your chosen plants.



16ft Wide – and – 18ft Wide Polytunnels

“Designed by Growers... Built by Engineers!”

The 16ft wide and the 18ft wide are the first of our commercial range of polytunnels and are manufactured to the same high specification as our larger commercial polytunnels, using 50mm diameter Z35 high tensile galvanised steel hoops. Our 18ft wide polytunnels include roof stabilisers at each end for added structural security. The low overall height of these commercial polytunnels ensures a reduced environmental impact and a reduction in heating costs. 3ft 3in straight sides before the start of the gentle curve of the polytunnel provides ample headroom right up to the edge when working manually or with machines. Thriving tall plants and the use of staging do not present a problem of a lack of internal space in these sturdy structures.

16ft Wide Specification

Overall Height: 8ft 6in
Straight Side: 3ft 3in
Head Room at 1ft in from Side: 5ft 9in
Distance Over Hoop: 27ft 10in
Steel Diameter: 50mm –
Spec: Z35 high tensile galvanised

18ft Wide Specification

Overall Height: 8ft 6in
Straight Side: 3ft 3in
Head Room at 1ft in from Side: 5ft 9in
Distance Over Hoop: 29ft 6in
Steel Diameter: 50mm –
Spec: Z35 high tensile galvanised

www.premierpolytunnels.co.uk



COMMERCIAL POLYTUNNELS....



21ft Wide – and – 24ft Wide Polytunnels

“Taking polytunnels to another level!”

As the width of a polytunnel increases, so does its uses – from animal house, machinery store, barn, swimming pool cover, and fish pond cover to name just a few, and of course the growing of plants and crops on a commercial scale. The larger area of our 21ft wide and 24ft wide commercial polytunnels offers improved air circulation and ventilation, and the low overall height ensures a reduced environmental impact. 4ft straight sides before the start of the gentle curve of the polytunnel provides head room of 6ft 10in at just 1ft in from the side. The design of these impressive structures ensures outstanding performance in all conditions, using 50mm diameter Z35 high tensile galvanised steel hoops, and both corner and roof stabilisers at each end for added structural security.



21ft Wide Specification

Overall Height: 9ft 9in
Straight Side: 4ft
Head Room at 1ft in from Side: 6ft 10in
Distance Over Hoop: 34ft 9in
Steel Diameter: 50mm –
Spec: Z35 high tensile galvanised

24ft Wide Specification

Overall Height: 10ft
Straight Side: 4ft
Head Room at 1ft in from Side: 6ft 10in
Distance Over Hoop: 37ft 11in
Steel Diameter: 50mm –
Spec: Z35 high tensile galvanised



www.premierpolytunnels.co.uk