

COMMERCIAL POLYTUNNELS



As the width of a polytunnel increases, so does its uses...

From animal house, machinery store, barn, swimming pool cover and fish pond cover, to name just a few, and of course the growing of plants on a commercial scale.



www.premierpolytunnels.co.uk

The larger area of a commercial polytunnel offers improved air circulation and ventilation, and the low overall height ensures a reduced environmental impact and a reduction in heating costs.

Straight sides of 3ft 3in or 4ft before the start of the gentle curve of the tunnel provides ample head room right up to the edge when working manually or with machinery. Thriving tall plants and the use of staging do not present a problem of a lack of internal space in these sturdy structures.

Here at Premier PolyTunnels we pride ourselves on offering the very highest quality of commercial polytunnels.

All of our polytunnels are supplied as a complete unit ready for assembly onto a soil base.

A full range of additions are available and are highly recommended to enable you to customise and enhance your polytunnel to suit the needs of your chosen plants. (Please see additions listed in main brochure).

16FT WIDE POLYTUNNELS

The 16ft wide is the first of our commercial range of polytunnels and is built to the same high specification as all of our commercial tunnels - using the same strong, quality materials.

Supplied as a complete unit ready for assembly onto a soil base and includes ALL of the following:

- An all-steel framework - manufactured using **50mm** diameter hoops - including foundation tubes, hoops, corner stabilisers and ridge.
- Timber door frame and 5ft 11in **double** hinged doors at each end.
- A **new to the UK** 720 gauge/180 micron Thermal Anti Drip polythene cover, with a 5-year warranty against UV degradation.

16ft Wide Specification:

- Overall Height: 8ft 6in
- Straight Side: 3ft 3in
- Head Room at 1ft in from Side: 5ft 9in
- Distance Over Hoop: 27ft 10in
- Steel Diameter: 50mm
- Steel Specification: Z35 high tensile galvanised



18FT WIDE POLYTUNNELS

A popular commercial size, the 18ft wide polytunnel has five stabilisers at each end for added structural stability.

"Designed by growers - built by engineers!"

Supplied as a complete unit ready for assembly onto a soil base and includes ALL of the following:

- An all-steel framework - manufactured using **50mm** diameter hoops - including foundation tubes, hoops, corner stabilisers and roof stabilisers, and ridge.
- Timber door frame and 5ft 11in **double** hinged doors at each end.
- A **new to the UK** 720 gauge/180 micron Thermal Anti Drip polythene cover, with a 5-year warranty against UV degradation.



18ft Wide Specification:

- Overall Height: 8ft 6in
- Straight Side: 3ft 3in
- Head Room at 1ft in from Side: 5ft 9in
- Distance Over Hoop: 29ft 6in
- Steel Diameter: 50mm
- Steel Specification: Z35 high tensile galvanised



21FT WIDE POLYTUNNELS

The larger area of the 21ft wide commercial polytunnel offers improved air circulation, and the 4ft straight sides provide ample head room right up to the edge for taller, specialist plants and a comfortable working area. Although our 21ft wide standard polytunnels have unmatched stability, for those sites exposed to extreme weather conditions why not choose to 'Premier Upgrade' your polytunnel to include an even larger diameter of hoop (60mm).

Supplied as a complete unit ready for assembly onto a soil base and includes ALL of the following:

- An all-steel framework - manufactured using **50mm** diameter hoops - including foundation tubes, hoops, corner stabilisers and roof stabilisers, and ridge.
- Timber door frame and 5ft 11in **double** hinged doors at each end.
- A **new to the UK** 720 gauge/180 micron Thermal Anti Drip polythene cover, with a 5-year warranty against UV degradation.

21ft Wide Specification:

- Overall Height: 9ft 9in
- Straight Side: 4ft
- Head Room at 1ft in from Side: 6ft 10in
- Distance Over Hoop: 34ft 9in
- Steel Diameter: 50mm
- Steel Specification: Z35 high tensile galvanised



24FT WIDE POLYTUNNELS

The larger area of our 24ft wide polytunnel makes it a popular choice not only for growing on a commercial scale, but also for use as a swimming pool cover, fish pond cover, barn, machinery store, and many other uses. Although our 24ft wide standard polytunnels have unmatched stability, for those sites exposed to extreme weather conditions why not choose to 'Premier Upgrade' your polytunnel to include an even larger diameter of hoop (60mm).

"Taking polytunnels to another level!"

Supplied as a complete unit ready for assembly onto a soil base and includes ALL of the following:

- An all-steel framework - manufactured using **50mm** diameter hoops - including foundation tubes, hoops, corner stabilisers and roof stabilisers, and ridge.
- Timber door frame and 5ft 11in **double** hinged doors at each end.
- A **new to the UK** 720 gauge/180 micron Thermal Anti Drip polythene cover, with a 5-year warranty against UV degradation.



24ft Wide Specification:

- Overall Height: 10ft
- Straight Side: 4ft
- Head Room at 1ft in from Side: 6ft 10in
- Distance Over Hoop: 37ft 11in
- Steel Diameter: 50mm
- Steel Specification: Z35 high tensile galvanised

27FT WIDE & 30FT WIDE POLYTUNNELS

Our 27ft wide and 30ft wide commercial polytunnels are supplied as complete units with all essential additions. No hidden extras - the items you need to construct one of these polytunnels are included as standard. The design of these structures ensures outstanding performance in all conditions, using 60mm diameter steel hoops, and including larger diameter steel corner and roof stabilisers at each end for added structural security. Base Rails are required to fit the polytunnel cover - trenching is not an option due to the distance over the hoop. Timber Base Rails are supplied as standard.

Also included is a Triple Ridge for additional and essential longitudinal strength.

Due to the size of this structure, we recommend the foundation tubes are concreted in position.

Supplied as a complete unit ready for assembly onto a soil base and includes ALL of the following:

- An all-steel framework - made using **60mm** diameter hoops - including foundation tubes, hoops, corner stabilisers and roof stabilisers, and Triple Ridge.
- Timber door frame and 8ft wide x 7ft high **double** hinged doors at each end.
- A **new to the UK** 720 gauge/180 micron Thermal Anti Drip polythene cover, with a 5-year warranty against UV degradation.
- Timber Base Rails for fixing the polythene cover.

27ft Wide Specification:

- Overall Height: 10ft 5in
- Straight Side: 3ft 3in
- Head Room at 1ft in from Side: 5ft 5in
- Distance Over Hoop: 39ft 4in
- Steel Diameter: 60mm
- Steel Specification: Z35 high tensile galvanised

30ft Wide Specification:

- Overall Height: 11ft
- Straight Side: 3ft 3in
- Head Room at 1ft in from Side: 5ft 5in
- Distance Over Hoop: 43ft 6in
- Steel Diameter: 60mm
- Steel Specification: Z35 high tensile galvanised

